



Restore

"The Ultimate Floor Cleaner / Restorer"

(Concentrated Restoration Product)


- **Eliminates Buildup**
- **Saves Time and Labor**
- **Deep Cleaning Formula**

Restore is a High Speed cleaner/maintainer for automatic or mop on use. Floors maintained with Restore can be spray buffed or high speed burnished. Restore repairs scuffing, scratching while leaving a burnishable micro layer that burnishes to a brilliant gloss. The economy can be seen when only 2 oz per gallon are required for daily maintenance.

Typical Properties:

Non-Volatile Solids (ASTM D2834)	30% minimum
Slip Resistance (ASTM D2047)	>0.50 COF
Flammability	Non-flammable
Color	Green
Removability (ASTM D1792)	Exceeds
pH (ASTM E70):	
Concentrate	10.0-11.5
2oz/gallon	8.5 - 9.5
Soil Resistance (ASTM D3206)	Excellent
Freeze Thaw (ASTM D3209)	Passes
Weight per gallon	8.5 lbs

Material Safety Data Sheet



Section I Company Information

Product Name: Restore

Company Name: Liquid Solutions Of America
Address: 2155 Stonington Ave. Hoffman Estates. IL 60195
Phone: 630-855-8010
Emergency: 630-247-0801

Proper Shipping Name: Non Regulated
Identification No: Not Applicable
Hazard Class: Not Applicable
Generic Description: Floor Finish Concentrate

Section II Hazardous Ingredients

CAS No	Ingredient	%	TLV
111773	DEG Methyl Ether	< 5	NE
26027383	Nonionic Surfactant	<30	NE

Section III Physical Data

Boiling Point: 212 F Specific Gravity: 1.019
Vapor Pressure: Not Determined Percent Volatile: N/A
Vapor Density: Less than Air H2O Solubility: Complete
Evaporation Rate: Slower than n-Butyl Acetate
Appearance & Odor: Clear liquid, citrus odor
VOC: 135 g/l (1.13 Lb/gal)

Section IV Fire & Explosion Data

Flash Point: None
Extinguishing Media: Foam or carbon dioxide or dry chemical.
Firefighting Procedure: Wear self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode when fighting fires.

Section V Health Hazard Data

Eyes: Can cause mild to moderate irritation.
Skin: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation.
Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
First Aid Procedures:
Eyes: Irrigation of the eye immediately with water for ten minutes is good safety practice.
Skin: Wash off in flow water or shower. Wash clothing before reuse.
Inhalation: Remove to fresh air if effects occur. If respiration stops, give mouth-to-mouth resuscitation. Administer oxygen if available. Call physician and/or transport to medical facility.
Ingestion: Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glassed of water or by sticking finger down throat. Do not give anything by mouth if the person is drowsy, unconscious or has no gag reflex.

Section VI Reactivity Data

Hazardous Polymerization: Will not occur
Stability: Stable
Incompatibility: Avoid strong oxidizing agents.

Section VII Spill & Leak Procedures

Response to spills: Stop discharge, if it can be performed safely, and contain material. If a substantial quantity is spilled, recover with pump or vacuum. Otherwise, use an absorbent material. Place contaminated material in a suitable container for disposal. Do not flush to sewer, stream or other bodies of water.

Section VIII Protective Equipment

Respiratory Protection: If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air supplied respirator is advised. Engineering or administrative controls should be implemented to reduce exposure.
Ventilation: Provide sufficient ventilation to maintain exposure below TLV(s).
Protective Gloves: Wear chemical resistant gloves such as nitrile rubber.
Eye Protection: Chemical splash goggles are advised.
Other Protective Equipment: Wear impervious clothing and boots.

Section IX Special Precautions

Precautions to be taken in Handling and storage: Handle with reasonable care. Avoid breathing vapors. Store in a cool dry place. Dispose of empty containers in accordance with local, state and federal guidelines. This product contains DEG Methyl Ether which is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372.

Warranty Information - Please Read Carefully:

Liquid Solutions Of America believes that the information in this literature is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application to determine its performance, efficacy and safety. Liquid Solutions Of America provides the sole warranty that the product will meet our current sales specifications. Your exclusive remedy and Liquid Solutions Of America only liability for breach or warranty is limited to refund of the purchase price or replacement of any product shown to be other than as warranted, and expressly disclaims any liability for incidental or consequential damages.

Prepared: 5/7/98
Revised: 1/03/04