



Innovative Cleaning Systems  
[www.tornadovac.com](http://www.tornadovac.com)

---

**ELECTRIC JUMBO EXTERNAL FILTER WET/DRY VACUUMS**



SINGLE ELECTRIC JUMBO  
DUAL ELECTRIC JUMBO

# ELECTRIC JUMBO EXTERNAL FILTER WET/DRY VACUUMS

High-speed bulk recovery, with 55-gallon steel drums for industrial applications

It is a simple principle: the higher the c.f.m. a vacuum generates, the better suited it is for recovering dry debris and bulk material. Tornado's electric powered jumbo vacuum systems are designed to face the rigors of industrial applications. The Single Electric Jumbo has a 2.25 HP powerhead mounted on a steel, rolled-top 55-gallon drum. An external poly bag is mounted on a support rod and serves as a final filter. The majority of the debris, including small particles, is actually recovered in the steel drum. The Dual Electric has an additional powerhead for added c.f.m. and two external poly filter bags.

Both the Single and the Dual Electric Jumbo comes standard with a drum and a four-wheeled steel dolly with convenient transport handle.

Electric Jumbo Vac Systems are appropriate for use in recovering heavy solid debris such as metal shavings and chips, sand, sawdust, and powder. The units are also effective in recovering water and cutting oil. A liquid shut-off float can be added to either unit. Attachment sets are required for operation and are sold separately.



**95954 Single Electric Jumbo**  
Comes complete with 2.25 HP powerhead, drum, filter, and dolly. Tornado's Jumbo vac systems are tailored for the maintenance professional faced with the demands of industrial applications.



**95960 Dual Electric Jumbo**  
Features an additional 2.25 HP powerhead and poly bag for recovery of heavier debris such as heavy machine oil and metal shavings and chips.



**Rugged**  
The 55-gallon, rolled-top, ribbed steel drum is superior to plastic or stainless steel tanks for heavy duty applications. The drum also features an industrial gate valve for ease in emptying liquids.

**CFM vs. Waterlift** Many competitive vacuum systems use waterlift as the primary measure of effectiveness and power. In a heavy industrial application, however, such vacs may lack sufficient airflow (cubic feet per minute, or CFM) to meet requirements. A unit's CFM tells the true story of its capability in bulk recovery environments. With high-levels of airflow (up to 340 CFM on the Dual Jumbo), a Tornado Electric Jumbo Vac System is ideal for rapid, efficient high-volume debris recovery.

#### Mobile

Despite their size and power, Tornado Jumbo vacs are highly portable, thanks to a four-wheeled dolly, included standard.



## ELECTRIC JUMBO WET/DRY APPLICATION GUIDE (★ = Excellent; ✓ = Good)

| MODEL    | CATALOG NUMBER | WATER | CUTTING OIL | MACHINE OIL | HEAVY MACHINE OIL | LIGHT SOLID DEBRIS | HEAVY SOLID DEBRIS | SAWDUST | POWDER | ULTRA FINE POWDER | SAND | OIL DRY | METAL SHAVINGS AND CHIPS |
|----------|----------------|-------|-------------|-------------|-------------------|--------------------|--------------------|---------|--------|-------------------|------|---------|--------------------------|
| SE JUMBO | 95954          | ✓     | ★           | ✓           |                   | ★                  | ✓                  | ★       | ★      | ★                 | ✓    | ✓       | ✓                        |
| DE JUMBO | 95960          | ✓     | ★           | ★           | ✓                 | ★                  | ★                  | ★       | ★      | ★                 | ★    | ★       | ★                        |

## PRODUCT SPECIFICATIONS

| MODEL    | CATALOG NUMBER | 2.25 POWERHEADS | STATIC WATERLIFT | CFM (ORIFICE)       | POLY EXTERNAL FILTERS | FILTER AREA          | EFFECTIVE HORIZONTAL REACH |
|----------|----------------|-----------------|------------------|---------------------|-----------------------|----------------------|----------------------------|
| SE JUMBO | 95954          | One             | 51"              | 184 (2')            | One                   | 1874 in <sup>2</sup> | 30'                        |
| DE JUMBO | 95960          | Two             | 51"              | 243 (2') / 340 (3') | Two                   | 3748 in <sup>2</sup> | 50'                        |

## STANDARD REPLACEMENT COMPONENT PARTS

| MODEL    | CATALOG NUMBER | 55-GALLON DRUM | LARGE POLY FILTER | SUPPORT RODS   | 4-WHEEL DOLLY | ADAPTER |
|----------|----------------|----------------|-------------------|----------------|---------------|---------|
| SE JUMBO | 95954          | 95942          | 90378 (1 req.)    | 98049 (1 Req.) | 98088         | 90331   |
| DE JUMBO | 95960          | 95942          | 90378 (2 req.)    | 98049 (2 Req.) | 98088         | 90332   |

## OPTIONAL ITEMS AND ACCESSORIES FOR SINGLE ELECTRIC JUMBO

90637 includes the below items.

| MUFFLER* | LIQUID SHUT-OFF FLOAT | 1.5" WET/DRY ATTACHMENT SET W/STATIC HOSE | 1.5" x 15' NEOPRENE HOSE | 1.5" X 15' URETHANE STATIC CONDUCTIVE HOSE W/O SLEEVE | DOUBLE CURVED 1.5" WAND | 14" X 1.5" SQUEEGEE FLOOR TOOL | 14" X 1.5" FIBRE FLOOR TOOL | 18" x 1.5" ROUND NOZZLE | 1.5" HOSE ADAPTER |
|----------|-----------------------|---|--------------------------|---|-------------------------|--------------------------------|-----------------------------|-------------------------|-------------------|
| 90447    | 90569                 | 90637**                                   | 90191                    | 90688   | 90286                   | 90240                          | 90242                       | 90414                   | 90331             |

## OPTIONAL ITEMS AND ACCESSORIES FOR DUAL ELECTRIC JUMBO

90633 includes the below items.

| MUFFLER* | LIQUID SHUT-OFF FLOAT 2 REQUIRED | 2" WET/DRY ATTACHMENT SET W/POLY HOSE | 2" x 15' NEOPRENE HOSE | 2" X 10' POLY HOSE W/OUT SLEEVE*** | 2" DOUBLE CURVED WAND | 12" X 2" FLOOR GULPER TOOL | 22" X 2" SQUEEGEE FLOOR TOOL | 18" X 2" ROUND NOZZLE | 2" HOSE ADAPTER |
|----------|----------------------------------|---------------------------------------|------------------------|------------------------------------|-----------------------|----------------------------|------------------------------|-----------------------|-----------------|
| 90447    | 90569                            | 90633**                               | 90311                  | 90312                              | 90327                 | 90320                      | 90317                        | 90444                 | 90332           |

\* Eliminates need for external filter in wet pick-up. Should not be used for dry recovery.

\*\* Other attachment sets are also available in the Tornado Buyers Guide.

\*\*\* Please note: poly hoses are not oil resistant. When recovering oils, and additional Neoprene hose, which is oil and abrasive resistant, should be purchased.



Tornado Industries • 7401 W. Lawrence Ave., Chicago, IL 60706 • 1-800-VACUUMS or (708) 867-5100 Fax: (708) 867-6968  
Visit our web site at: [www.tornadovac.com](http://www.tornadovac.com)